

MOBILE GRINDING AND HULLING UNIT



THE MINI-MILL OF THE BUSH

For the preparation of flour: maize, sorghum, millet, etc.

SPECIFICATIONS

ONE BABY "N" GRINDER:

- 2 inlets: by hopper for cereals and chute for tubers
- 28-litre hopper with flow regulator
- rotor rotation speed: 6000 rpm
- V-belt drive and protective housing
- motor base with tilting tension system with 7.5
 HP 380V three-phase electric motor
- electrical control panel comprising an ammeter, a circuit breaker and a y-delta starter

A DMS 500 "N" HULLER:

- feed hopper, milling and flow rate regulator
- 1 grid Ø1.2 mm
- V-belt drive and protective housing
- motor base with tilting tension system with 7.5
 HP 380V three-phase electric motor

electrical control panel comprising an ammeter, a circuit breaker and a y-delta starter

ONE 900 KG GVRW BRAKED TRAILER:

- overall dimensions LxWxH: 3.9x2x2.1 m
- braked coupling, one braked 900 kg axle, 2 175R14C wheels
- sheet metal front, galvanized sheet floor
- jockey wheel at the front, 2 props at the rear
- tarpaulin opening on 3 sides with removable frame
- EDF blue colour

ONE GET 22 GENERATOR SET:

- DEUTZ engine, three cylinders, F3L2011, 20 kVA
- silencers
- air cooling
- integrated 55-litre diesel tank
- 12 volt battery
- NSM alternator
- the whole mounted on a chassis with antivibration mounts
- electrical control panel with circuit breaker, 5-pin three-phase socket, 3-pin single-phase socket, voltmeter, ammeter, hour meter and motor safety key ignition, emergency stop button, circuit breaker at the head and terminal block
- weight: 510 kg
- dimensions: L=1.6 x W=0.85 x H=1.4



Equipment intended for export outside the EC

The technical specifications may be subject to change without notice



47170 POUDENAS - FRANCE

Tel.: +33 (0)5 53 65 73 55 Fax: +33 (0)5 53 97 33 05 e-mail: tropica@electra.fr Internet: www.electra.fr